



DOW[®]

A pipe's dream

Why choose PE-RT over PEX for plumbing pipe?

Flexibility, efficiency and performance have made polyethylene a popular material choice for plumbing pipe, in new construction and rehab projects. But which kind of polyethylene is best? There's cross-linked polyethylene (PEX). And there's Polyethylene of Raised Temperature (PE-RT). Both offer outstanding performance. **But it's PE-RT that offers processing and sustainability advantages that PEX can't.**

The difference? PE-RT resins are manufactured using bimodal technology, giving the material inherent properties required to perform in raised temperature and chlorinated potable water conditions. Polyethylene resins used to make PEX pipe must undergo a post-extrusion cross-linking treatment in order to achieve the required strength in the finished pipe. That extra step increases production time and overall costs.


Our HYPERTHERM™ Polyethylene of Raised Temperature (PE-RT) Resins offer outstanding performance attributes for plumbing pipe systems:

- Excellent toughness and flexibility
- Durable, virtually leak-free performance
- Corrosion resistance
- Light weight
- Ease of installation
- Lower overall cost versus metal pipe
- Excellent taste and odor characteristics
- Little or no maintenance required

Strong. Reliable. Sustainable.

HYPERTHERM™ PE-RT meets ASTM F2769 performance requirements, which are the same as the ASTM F876 standards used for PEX.⁽¹⁾ Dow's PE-RT resins also offer CL5 oxidative resistance classification, excellent hydrostatic strength and strong performance that's comparable to PEX. Dow's PE-RT resins also meet NSF 14 and 61 requirements.

Simple tooling on existing extrusion lines makes for easy resin processing. No cross-linking means fewer steps and less energy to manufacture. Extreme durability means fewer repairs and replacement over the life of the pipe system. **And, unlike a crosslinked material, PE-RT is 100% recyclable, making HYPERTHERM™ PE-RT the sustainable choice in plumbing pipe.**



Hypertherm™

PE-RT resins by 

Convinced? For more information, contact your Dow representative.

⁽¹⁾ASTM F2769-18, Standard Specification for Polyethylene of Raised Temperature (PE-RT) Plastic Hot and Cold-Water Tubing and Distribution Systems, ASTM International, West Conshohocken, PA, 2018, www.astm.org

®™Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

For more information about Dow, visit www.dow.com/about. To contact a Dow representative, visit, www.dow.com/contact.

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

THIS INFORMATION IS OFFERED IN GOOD FAITH FOR YOUR CONSIDERATION, BUT WITHOUT GUARANTEE OR WARRANTY (EXPRESS OR IMPLIED), AS ANALYTICAL CONDITIONS AND METHODS OF USE OF THE INFORMATION AND MATERIALS DESCRIBED HEREIN MAY VARY AND ARE OUT OF DOW'S CONTROL. ALTHOUGH THIS INFORMATION IS BASED ON DATA DOW BELIEVES TO BE RELIABLE AND ACCURATE, WE DO NOT INTEND FOR YOU TO USE, AND YOU THEREFORE SHOULD NOT CONSTRUCE, THE CONTENTS OF THIS DOCUMENT AS BUSINESS, TECHNICAL OR ANY OTHER FORM OF ADVICE. WE RECOMMEND YOU DETERMINE THE SUITABILITY OF THE INFORMATION AND MATERIALS DESCRIBED HEREIN BEFORE ADOPTING OR USING THEM ON A COMMERCIAL SCALE. DOW ASSUMES NO LIABILITY IN CONNECTION WITH THE USE OF THIS INFORMATION.

This document is intended for use in North America.
© 2021 The Dow Chemical Company